



### Allo 2" & 4"

---



#### Description:

LED anti-glare downlight comes complete with an external driver in a junction box. Commercial grade quality with architectural design.

Air Tight & IC Rated: Deep anti-glare design . Fast & Easy Installation: Save labor cost. Junction Box Included:

---

**Model:** DNLRXX11X5CCXXGS

---

#### Optical:

CCT:	5CCT Tunable, 27K/30K/35K/40K/50K
Lumen out put::	1000-1100
LED :	COB
CRI:	>90Ra

---

#### Electrical:

Rated Power:	9W / 12W / 15W
Input voltage:	100-130V AC, 50/60HZ
Beam angle:	24° / 36°

---


#### Life:

Lifespan:	30,000hrs
Warranty:	2 Years

---

#### General:

Dimmable Solution:	Triac dimming 5-100%
Power Factor:	>0.9
Type:	IC , Airtight
Body:	Die cast aluminum alloy for optimal heat dissipation
Certification:	cETLus





## Allo 2" & 4"

### PRODUCT TYPES

Size&Shape	Input Power	Lumen	Halogen Equivalent
2" Round	9 W	600-700	60W
2" Square	9 W	600-650	60W
4" Round	12 W	1000-1100	90W
4" Round	15 W	1200-1350	90W
4" Square	12 W	1000-1100	90W
4" Square	15 W	1200-1350	90W

Family series	Shape	Reflector	Color	Size	Wattage	CCT
DNL	S: Square	B: Baffle	W: White	04:4"	09:9W	5C:5CCT
	R: Round	S: Smooth	B: Black	02:2"	12:12W	



## Allo 2" & 4"

### PROUDUCT SIZE

Size&Shape	Dimension	Cutout Size
2" Round	Φ80*67mm	Φ70mm
2" Square	Φ80*67mm	Φ70mm
4" Round	Φ122*67mm	Φ102-108mm
4" Square	Φ122*77mm	Φ102-108mm





## Allo 2" & 4"

